

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date  
12 May 2005 (12.05.2005)

PCT

(10) International Publication Number  
**WO 2005/043126 A3**

(51) International Patent Classification<sup>7</sup>: G01N 1/00

(21) International Application Number:  
PCT/US2004/036705

(22) International Filing Date: 27 October 2004 (27.10.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/514,803 27 October 2003 (27.10.2003) US

(71) Applicant (for all designated States except US): DREXEL UNIVERSITY [US/US]; 32nd & Chestnut Streets, Philadelphia, PA 19104 (US).

(72) Inventors; and


(75) Inventors/Applicants (for US only): SHIH, Wan, Y. [US/US]; 641 Heather Lane, Bryn Mawr, PA 19010 (US). SHIH, Wei-Heng [US/US]; 641 Heather Lane, Bryn Mawr, PA 19010 (US). SHEN, Zuyan [CN/US]; 3929 Powelson Avenue, 2R, Philadelphia, PA 19104 (US).

(74) Agent: DUNLEAVY, Kevin, J.; Knoble Yoshida & Dunleavy, LLC, Eight Penn Center, Suite 1350, 1628 John F. Kennedy Boulevard, Philadelphia, PA 19103 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

(54) Title: PIEZOELECTRIC CANTILEVER SENSORS

**WO 2005/043126 A3**



(57) Abstract: A piezoelectric cantilever with a non-piezoelectric, or piezoelectric tip useful as mass and viscosity sensors. The change in the cantilever mass can be accurately quantified by monitoring a resonance frequency shift of the cantilever. For detection, antibodies or other specific receptors of target antigens may be immobilized on the cantilever surface, preferably on the non-piezoelectric tip. For chemical detection, high surface-area selective absorbent materials are coated on the cantilever tip. Binding of the target antigen or analytes to the cantilever surface increases the cantilever mass. Detection of target antigens or analytes is achieved by monitoring the cantilever's resonance frequency and determining the resonance frequency shift that is due to the mass of the adsorbed target antigen on the cantilever surface. The use of a piezoelectric unimorph cantilever allows both electrical actuation and electrical sensing. Incorporating a non-piezoelectric tip (14) enhances the sensitivity of the sensor. In addition, the piezoelectric cantilever can withstand damping in highly viscous liquids and can be used as a viscosity sensor in wide viscosity range.